




Enecsys Micro Inverters SMI-D360W-72



Maximized Energy Harvest

Improved Safety

Increased Lifetime & Reliability

Enhanced Monitoring Capability

Simplified PV Array Design & Installation

Enecsys develops, manufactures and markets world leading, highly reliable grid-connected solar micro inverters and monitoring systems that offer an outstanding value proposition for solar PV systems.

Enecsys Ltd
Harston Mill, Royston Rd
Cambridge, CB22 7GG, UK
Tel. +44 1223 792101
Fax.+44 1223 792103

Enecsys Europe GmbH
Louisenstraße 65
61348 Bad Homburg, Germany
Tel. +49 6172 8552430
Fax.+49 6172 8552440

Enecsys LLC
275 Shoreline Drive, Suite 200
Redwood Shores, CA 94065, USA
Tel. +1 855-ENECSYS
(Toll Free in USA)
Tel. +1 650-730-5700

Enecsys Taiwan
9F, No.8, Ln. 321, Yangguang St
Neihu District, Taipei City 114
Taiwan (R.O.C.)
Tel. +886-2-2627-6118

Enecsys France
Tel. +33 (0)4 13 68 09 64



Technical Specification

SMI-D360W-72-(see "ordering information" for region code)

Input Data (DC)	
Nominal Input Power	360W
Recommended Input Power (STC)	380W
Maximum DC Voltage	54V
Minimum DC Voltage	27V
MPPT Voltage Range	30V - 42V
Maximum Input Current	13.4A
Output Data (AC)	
Maximum AC Output Power	340W
Nominal AC Output Current	1.48A
Nominal Output Voltage	230V
Nominal Frequency	50Hz
Power Factor	> 0.95
Total Harmonic Distortion	< 5%
Efficiency	
Euro Efficiency	93.5%*1
Peak Efficiency	95.4%
Maximum Night Power Consumption	< 30mW
Mechanical Data	
Operating Temperature Range	-40°C to +85°C
Enclosure Rating	IP66
Dimensions (LxHxW)	262mm x 160mm x 35mm*2
Weight	1.8kg
Cooling	Natural Convection
Features & Compliance	
Safety Class Compliance	CE, pr EN 62109-1
EMC (Emission & Immunity) Compliance	EN61000-6-3, EN61000-6-1
Grid Connection Compliance	G83/ 1-1*3, VDE 01 26-1, IEC 61727, IEC 62116
Communication	Zigbee IEEE 802.15.4
Connector	MC4
PV Compatibility	Compatible with most 72 cell modules
Warranty	20 Years (at full ambient temperature range)
Technology	Thin film capacitors
Isolation	Galvanic

Ordering Information

Region code	Region
-DE	Germany
-FR	France
-IT	Italy
-UK	United Kingdom

*1 - Efficiency maintained over full ambient temperature range from -40°C to +85°C and at nominal output power
 *2 - Without the mounting bracket
 *3 - In accordance with the Enecsys installation guidelines (please refer to the Enecsys Installation Manual)
 All technical specifications contained within this document are subject to change without prior notice