


Mounting systems for solar technology



K2 SYSTEMS
ELEVATION SYSTEMS
TRIANGLE SYSTEM

TRIANGLE SYSTEM

- The K2 Triangle System can be used on flat and sloped roofs
- Each triangle is an optimised solution through project-specific customisation
- Optimum elevation angles possible for any roof
- High flexibility - for all module types
- High-quality materials - for long service life
- Modular structure suitable for any system size
- Ballast using PE plate or loading system



Tittmann Solar | State Theatre Stuttgart - Germany
System: 112 kW | Triangle System

Technical data



Field of application	Flat and sloped roofs
Roofing	Suitable for virtually all types
PV modules	Suitable for all standard module types
Module orientation	Vertical / horizontal (with cross bracing)
Material	Aluminium (EN AW-6063 T66)
Connecting elements	Stainless steel screws A2-70 / aluminium
Roof connection	Screw connection, clamping, ballasting
Static principles	Calculation principles in accordance with Eurocode 9 - dimensioning and construction of aluminium structures, Load assumption in accordance with DIN 1055 / Eurocode 1
System components	Pre-assembled triangle, mid and end clamp sets, SolidRail range, PE panel



Elpo | Seis - Italy
System: 5,76 kW | Triangle System

SERVICE-HOTLINE
+49 (0)7152 3560-0
www.k2-systems.com

Product Sheet Triangle | GB1 | 0112 | Subject to change
Product illustrations are exemplary illustrations and may differ from the original.

